

# STANDALONE SMARTLOCKS and HOTEL LOCKS



<b>HBL400</b> SMARTLOCKS Aluminum Alloy Face: 50 Fingerprint: 100 MF Card: 50 Password: 50 Administrators: 5 User Capacity: 250 Door bell function	<b>TL800</b> SMARTLOCKS Aluminum Alloy Fingerprint: 100 MF Card: 50 Password: 50 User Capacity: 200 Door bell function	<b>TL700</b> SMARTLOCKS Aluminum Alloy Fingerprint: 100 MF Card: 100 Password: 50 User Capacity: 250 Doorbell Function Battery: 4x AA alkaline batteries	<b>AL40B</b> SMARTLOCKS Outdoor Bluetooth Lock User Capacity: 100 Fingerprint: 100 Password: 100 MF card capacity: 100	<b>GL300</b> SMARTLOCKS User Capacity: 100 Fingerprint: 300 MF Card: 300 Password: 300 Remote Key Function Doorbell Function
<b>LH7500</b> HOTEL LOCKS Zinc Alloy Casing 13.56mhz MIFARE-1 Door Thickness: 35-45 mm Backset: 62.5 mm	<b>LH6800</b> HOTEL LOCKS Zinc Alloy Casing 13.56mhz MIFARE-1 Door Thickness: 35-45 mm Backset: 62.5 mm	<b>LH6500</b> HOTEL LOCKS Zinc Alloy Casing 13.56mhz MIFARE-1 Door Thickness: 35-45 mm Backset: 62.5 mm	<b>LH6000</b> HOTEL LOCKS Zinc Alloy Metal Casing 13.56mhz MIFARE-1 Door Thickness: 35-55 mm Backset: 62.5 mm	<b>LH5000</b> HOTEL LOCKS Zinc Alloy Metal Casing 13.56mhz MIFARE-1 Door Thickness: 35-45 mm Backset: 62.5 mm
<b>LH4000</b> HOTEL LOCKS Zinc Alloy Metal Casing 13.56mhz MIFARE-1 Door Thickness: 35-45 mm Backset: 70 mm	<b>ENERGY SAVING SWITCH-MIFARE</b> ACCESSORIES • AC220V/AC110V • 30A • Delay time: 12 sec • Card type: 13.56 MHz ISO14443A	<b>CR60W</b> ACCESSORIES Card Issuer Reader for Hotel Lock Mifare Card	<b>MIFARE CARD(S70)</b> ACCESSORIES 13.56Mhz Mifare One Card Standard MF1 S70 (4 Kbyte) EEPROM	<b>SOFTWARE</b> <b>ZKBS-HOTEL-P100</b> Basic Package -Supports up to 100 doors max. <b>ZKBS-HOTEL-P50</b> Basic Package -Supports up to 50 doors max. <b>ZKBS-HOTEL-P25</b> Basic Package -Supports up to 25 doors max.



# GREEN LABEL Time & Attendance Terminals & Software

<b>G4</b> Firmware: T&A Push SDK LCD: 7" Touchscreen Face Cap. : 10,000 Fingerprint Cap.: 10,000 MF Card Cap.: 10,000 Record Cap.: 1,000,000 Comm. : TCP/IP, Wi-Fi, USB-Host, Wiegand In/Out	<b>G3/ID</b> Firmware: T&A Push SDK LCD: 3.5" TFT colored Face Cap. : 3,000(1:N) 4000(1:1) Fingerprint Cap.: 5,000 ID Card Cap.: 10,000 Record Cap.: 100,000 Comm. : TCP/IP, Wiegand In/Out, SRB	<b>G2/ID</b> Firmware: T&A Push SDK LCD: 3.5" TFT colored Fingerprint Cap.: 20,000/40,000 ID Card Cap.: 20,000 Record Cap.: 200,000 Comm. : TCP/IP, Wiegand In/Out	<b>G1/ID</b> Firmware: T&A Push SDK LCD: 2.8" TFT colored Fingerprint Cap.: 5,000 ID Card Cap.: 15,000 Record Cap.: 100,000 Comm. : TCP/IP, USB-Host, Wiegand Out	<b>ZKBIOSECURITY</b> SOFTWARE <b>ZKBS-TA-P5</b> Basic Package -Supports up to 5 Devices <b>ZKBS-TA-P10</b> Basic Package -Supports up to 10 Devices <b>ZKBS-TA-P25</b> Basic Package -Supports up to 25 Devices
---	---	--	---	---

# TIME & ATTENDANCE BIOMETRICS

<b>MV560-VL-ID/ADMS/WIFI</b> Display : 2.8-inch Face Cap. : 500 Card Cap. : 1,000 Transactions : 150,000 Comm. : TCP/IP, WIFI, USB-Host	<b>EFACE10/ID/WIFI/ADMS</b> Face Cap. : 3000 Fingerprint Cap.: 3000 Card Cap. : 10,000 Transactions : 100,000 Comm. : TCP/IP, WIFI, USB-Host	<b>UFACE800/ID/ADMS/BATTERY</b> Face Cap. : 3000 Palm : 3000 Fingerprint Cap.: 4000 Card Cap. : 10,000 Transactions : 100,000 Comm. : TCP/IP, USB-Host, Wiegand	<b>MB460/ID/ADMS</b> Face Cap. : 1500 fingerprint Cap.: 2000 Card Cap. : 2,000 Transactions : 100,000 Comm. : TCP/IP, USB-Host
<b>IN02-A/ID/ADMS</b> Fingerprint Cap.: 3000 Card Cap. : 10,000 Transactions : 100,000 Comm. : TCP/IP, USB(Host Client) RS232/485	<b>SILKFP-101TA/ID</b> Face Cap. : 3000 Card Cap. : 10,000 Transactions : 100,000 Comm. : TCP/IP, USB(Host Client)	<b>UA860/ID</b> User Cap. : 3500 fingerprint Cap.: 3000 Card Cap. : 2,000 Transactions : 50,000 Comm. : TCP/IP, USB-Hos, WIFI	<b>MB10-VL/ID</b> Face Cap. : 100 Fingerprint Cap.: 500 Card Cap. : 500 Transactions : 50,000 Comm. : TCP/IP, USB Host

# GREEN LABEL Standalone Access Control Devices, Controllers & Software

<b>PROFACE X</b> Firmware: AC Push SDK LCD: 8" Touchscreen Face Cap. : 30,000 ID/MF Card Cap.: 50,000 Record Cap.: 1,000,000 Comm. : TCP/IP, Wi-Fi, Wiegand In/ Out, SRB	<b>PRORF-T/ID</b> Firmware: AC Push SDK LCD: 2.4" Touchscreen ID Card Cap.: 50,000 Record Cap.: 100,000 Users Photo: 7,000 Event Photo: 3,000 Comm. : TCP/IP, Wi-Fi, USB-Host, Wiegand In/ Out, SRB	<b>INBIO460 PRO</b> Packaged Contents: 1 x Inbio460 Pro Controller - Firmware: Push SDK - Users: 30,000 - Records: 100,000 - Communication: TCP/IP - Software: ZKBioSecurity 1 x Metallic Box 1 x Power Supply	<b>INBIO260 PRO</b> Packaged Contents: 1 x Inbio260 Pro Controller - Firmware: Push SDK - Users: 30,000 - Records: 100,000 - Communication: TCP/IP - Software: ZKBioSecurity 1 x Metallic Box 1 x Power Supply	<b>INBIO160 PRO</b> Packaged Contents: 1 x Inbio160 Pro Controller - Firmware: Push SDK - Users: 30,000 - Records: 100,000 - Communication: TCP/IP - Software: ZKBioSecurity 1 x Metallic Box (Black) 1 x Power Supply	<b>ZKBIOSECURITY</b> SOFTWARE <b>ZKBS-AC-P100</b> Basic Package -Supports up to 100 Doors <b>ZKBS-AC-P75</b> Basic Package -Supports up to 75 Doors <b>ZKBS-AC-P50</b> Basic Package -Supports up to 50 Doors <b>ZKBS-AC-P25</b> Basic Package -Supports up to 25 Doors <b>ZKBS-AC-P10</b> Basic Package -Supports up to 10 Doors
--	--	---	---	---	---

<b>K40/ID</b> Fingerprint : 3000/1000 (SSR Function on) Card Cap. : 1,000 Transactions : 80,000 Comm. : TCP/IP, USB Host	<b>LX15</b> Display : 2.8TFT User Cap. : 500 fingerprint Cap.: 500 Transactions : 50,000 Comm. : TCP/IP, USB-Host	<b>ACCESSORIES</b> <b>12V MINI-UPS</b> Input : DC12V-2A Output : DC7-12V/0.8A Charge Time : ≥ 5H Discharge Time : 3 ± 0.8H Indicator light : red = Charging	<b>5V MINI-UPS</b> Input : DC5V-2A Output : DC5V/0.8A Charge Time : ≥ 7.5H Discharge Time : 3 ± 0.8H Indicator light : red = Charging
--	--	---	--

Philippine Distributor  
**PHITEQ**  
 ENTERPRISE INC.


Authorized Reseller:

# ACCESS CONTROL BIOMETRICS

# INBIO CONTROLLER PACKAGE

### SPEEDFACE-V4L

Display : 4" Colored touch screen  
 Face Cap. : 800  
 Palm Cap. : 800  
 Card Cap. : 1,000  
 Transactions : 50,000  
 Comm. : TCP/IP, WIFI  
 Wiegand, Input/output, RS485  
 Memory : 512RAM/512Flash




### MULTIBIO800-H/ID/ADMS

Display : 2.8 TFT Colored screen  
 Face Cap. : 1,500  
 Fingerprint Cap.: 4000  
 Card Cap. : 10,000  
 Transactions : 100,000  
 Comm. : TCP/IP, RS485  
 USB Host



### MULTIBIO800-ID/ADMS

Display : 2.8 TFT Colored screen  
 Face Cap. : 800  
 Fingerprint Cap.: 1,000  
 Card Cap. : 1,000  
 Transactions : 100,000  
 Comm. : TCP/IP, RS485  
 USB Host



### INBIO460 PACKAGE B

Packaged Contents:  
 • 1 x Inbio460 Controller  
 • 1 x Metallic Box  
 • Users: 30,000  
 • Records: 100,000  
 • Software: ZKAccess 3.5 (FREE)



### INBIO260 PACKAGE B

Packaged Contents:  
 • 1 x Inbio260 Controller  
 • 1 x Metallic Box  
 • Users: 30,000  
 • Records: 100,000  
 • Software: ZKAccess 3.5 (FREE)



### INBIO160 POE BUNDLE

Packaged Contents:  
 • 1 x Inbio160 PoE Controller  
 • 1 x Metallic Box  
 • Users: 30,000  
 • Records: 100,000  
 • Software: ZKAccess 3.5 (FREE)



### INBIO160 PACKAGE B

Packaged Contents:  
 • 1 x Inbio160 Controller  
 • 1 x Metallic Box  
 • Users: 30,000  
 • Records: 100,000  
 • Software: ZKAccess 3.5 (FREE)



### F22/MF

Fingerprint Cap.: 1500  
 Card Cap. : 5,000  
 Transactions : 30,000  
 Comm. : TCP/IP, WIFI, RS485  
 USB Host




### F22/ID

Display : 2.8" TFT LCD Color  
 Face Cap. : 1500  
 Palm Cap. : 4000  
 Card Cap. : 10,000  
 Transactions : 100,000  
 Comm. : TCP/IP, RS485  
 USB Host



### F21/ID

Display : 2.4" TFT colored screen  
 Keypad and Z2M20 coreboard  
 Fingerprint Cap.: 3000  
 Card Cap. : 5,000  
 Transactions : 30,000  
 Comm. : TCP/IP, WIFI, RS232/485  
 USB Host




### F18/ID

Display : 2.4" TFT-LCD Color  
 Fingerprint Cap.: 3000  
 Card Cap. : 5,000  
 Transactions : 30,000  
 Comm. : TCP/IP, RS232/485,  
 USB Host



### TF1700/ID

Display : 1.54" OLED screen,  
 IP65  
 Fingerprint Cap.: 3000  
 Card Cap. : 30,000  
 Transactions : 100,000  
 Comm. : TCP/IP, RS485,  
 USB Host




### SF400/ID

Display : 2.8" Colored  
 touch screen  
 Fingerprint Cap.: 1500  
 Card Cap. : 5,000  
 Transactions : 80,000  
 Comm. : TCP/IP, RS485,  
 USB Host



### SCR100/ID

Card Cap. : 30,000  
 Transactions : 50,000  
 Comm. : TCP/IP, RS232,  
 USB Host



## ACCESS CONTROL KIT

### SF400 KIT(E)

- 1 x SF400 (Access Control Device)
- 1 x AL-100 (Dropbolt Lock)
- 1 x PS901B (Centralized Power Supply)
- 1 x TLEB102-R (Non-Touch Exit Button with Remote)
- 10pcs Proximity Cards (White)
- 10pcs Proximity Tags (Blue)



### SF400 KIT(M)

- 1 x SF400 (Access Control Device)
- 1 x AL-100 (Dropbolt Lock)
- 1 x PS901B (Centralized Power Supply)
- 1 x TLEB102-R (Non-Touch Exit Button with Remote)
- 10pcs Proximity Cards (White)
- 10pcs Proximity Tags (Blue)




### PS902

- Power Supply without Battery Leads
- Input: 220V AC, 50Hz (110V optional)
- Output: 12V DC, 5A



### PS902B

- Power Supply with Battery Leads
- Input: 220V AC, 50Hz (110V optional)
- Output: 12V DC 5A
- \*Battery not included



## SLAVE READERS

### KR602M

- Read 13.56MHz Mifare card number or PIN
- Wiegand output 34bit
- Dimension: 86\*86\*20mm



### KR600E

- Read 125KHz Proximity ID card number
- Wiegand output 26bit
- Dimension: 75\*116\*16mm



### FR1500/MF

- RS485 Fingerprint Reader, Single gang.
- Standard: ID card.
- Optional: Mifare, HID, iclass card.



### FR1500/ID

- RS485 Fingerprint Reader, Single gang.
- Standard: ID card.
- Optional: Mifare, HID, iclass card.



### FR1300/ID

- Read Fingerprint, password and Proximity card
- Communication: RS485 with INBIO controller or Fingerprint devices
- DIP switch for RS485 address



## ACCESSORIES

### SLK20R

Desktop USB Enrollment device, based on SLK20M embedded module, fingerprint acquisition, support Win10/8/7, support USB only. Firmware version: V2.30.



### ZK8500R/MF

USB interface Capture fingerprint template and read ID/MF card serial number for Central management



### ZK8500R/ID

USB interface Capture fingerprint template and read ID/MF card serial number for Central management



### CR20M

Read 13.56 Mhz mifare card number, USB interface



### CR20FE

Read 125Mhz proximity card number USB interface



## SLAVE READERS EXIT BUTTONS

### FR1200/ID

- Read Fingerprint and Proximity card
- Communication: RS485 with INBIO controller or Fingerprint devices
- DIP switch for RS485 address



### EX-806B

- Emergency Keyswitch
- NO/NC/COM
- with key
- Size: 90Lx90W (mm), 2A 250V



### EX-801A

- Small metallic push button
- Size: 800A
- 81L \* 28W \* 20T(mm)



### EX-802

- RS485 Fingerprint Reader, Single gang.
- Standard: ID card.



### TLEB102-R

- Non touch Exit Sensor with Remote Key (Diffused Detection)
- NO NC COM relay output
- Size: 118L\*70W(mm)



## ELECTRIC DROPBOLTS AND BRACKET AL-280 MAGNETIC LOCK and BRACKETS

### AL-300



### AL-200PZ



### AL-100PF



### AL-180D



### AL-180M



### AL-180



### AL-180DPL



### AL-180PL



### AL-180PZ



### AL-180PU



## C3 CONTROL PACKAGE

### C3-400 PACKAGE B

Packaged Contents:  
 • 1 x C3-400 Controller  
 • Users: 30,000  
 • Records: 100,000  
 • Software: ZKAccess 3.5 (FREE)



### C3-200 PACKAGE B

Packaged Contents:  
 • 1 x C3-200 Controller  
 • Users: 30,000  
 • Records: 100,000  
 • Software: ZKAccess 3.5 (FREE)



### C3-100 POE BUNDLE

Packaged Contents:  
 • 1 x C3-100 POE Controller  
 • Users: 30,000  
 • Records: 100,000  
 • Software: ZKAccess 3.5 (FREE)



### C3-100 PACKAGE B

Packaged Contents:  
 • 1 x C3-100 Controller  
 • Users: 30,000  
 • Records: 100,000  
 • Software: ZKAccess 3.5 (FREE)



## AL-500 MAGNETIC LOCK and BRACKETS

### AL-500D(LED)



### AL-500(LED)



### AL-500DPL



### AL-500PL



### AL-500PZ

